

VEXTOR

Pan-Tilt Systems



The Vextor® VX-101 pan-tilt head is a quiet, easy to use unit. It will find acceptance in many areas, a few of which are teleconferencing, city council meeting broadcasting, distance learning, surgical documentation, local access cable broadcasting, and entertainment venues.

The VX-101's compact size allows for placement in out of sight areas, so as not to disturb participants in meetings and classes. It has an available wall mount or ceiling mount adapter to fit into many different applications.

The head has very good motion characteris-

VEXTOR® VX-101 PAN TILT HEAD VEXTOR® system compatible

Can link up to 32 total devices on one RS-485 control chain or be directly controlled by computer using RS-232 protocol

Worm gear driven for smooth, accurate, repeatable performance

Vector solving operation in manual or preset modes

128 presets per head, stored internally in non-volatile memory

Extremely quiet operation in upright or inverted positions

Will handle camera and lens combinations weighing up to 12 lbs.

Built in 12VDC 5A camera power supply

Optional VX-CCB-101 camera control module for integrated remote camera control of selected Hitachi, Sony cameras using Vextor® system controllers, PC software, or AMX and Crestron control systems

Control software available for Windows NT/2000/XP™ compatible PC's

5 pin connector on base allows for easy connection of power and control lines-**NO SOLDERING NEEDED!**

Video and Genlock connections made at base are passed through head to camera--no cables to get caught when panning or tilting

Pre-built camera control /power harness, and camera mount provided with each head

All needed connectors for power and control are included

tics, with a range of motion of up to 360° in pan and +/- 120° in tilt. The unit has three overall speed ranges at up to 30° per second in both pan and tilt. Speed is completely variable from zero to full based on proportional digital joystick input.

Up to 128 different preset combinations of position and lens settings can be memorized by the head. All are stored in non-volatile memory inside each head, and can easily be recalled at any time.

The Vextor® VX-101 is for camera / lens combinations of up to 12 pounds (5.4 kg).



SPECIFICATIONS

Weight: about 9 pounds (4.0 kg)

Maximum load: 12 pounds (5.4 kg)

Pan range: ± 179 degrees

Tilt range: ± 120 degrees

Pan and tilt speed: 0 to 30° per second, infinitely variable

Accuracy of preset position recall: ± 5 arc minutes (.083 degrees)

Max. number of preset positions: 128

Requires 24VDC power, minimum 2.5A: max draw with camera: 4.5

Worm gear drive with high-torque stepper motors

Uses RS-485 or RS-232 communications protocol; no adapters required

Provides 12VDC camera power at up to 5 amps (cameras drawing more than 2 amps require usage of PS24-6.5 power supply)

Vextor™ products are designed and manufactured and distributed by Display Devices Inc., Arvada CO USA 80003

Call toll free 1-877-862-6865 for a dealer near you: outside the Continental US, call 1-303-412-0399

OPTIONAL ACCESSORIES

VX-500TS Color TouchScreen controller

VX-C desktop pan-tilt controller

VX-CC desktop camera controller

VX-CCB-101 camera control module (internal option in head)

PS-24-12 quad 3A output power supply

PS-6.5 single 6.5A output power supply

VX-SB "Shot Box" motion control recorder

VX-T2 one input, six output control and power splitter box

VX-WM-L wall mount arm

VX-CMA-101 ceiling mount adapter base for 1.5" NPT pipe

VX-AAM Auto answer modem, includes one VX-RSA serial adapter

VX-MP-1 control multiplexer; allows multiple controllers on single RS-485 backbone

VX-CSI contact closure interface